



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 334 703 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
13.08.2003 Bulletin 2003/33

(51) Int Cl.7: **A61F 2/44**

(21) Application number: **03002588.6**

(22) Date of filing: **07.02.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT SE SI SK TR**
Designated Extension States:
AL LT LV MK RO

(72) Inventors:
• **Nekozuka, Yoshio**
Sapporo-shi, Hokkaido (JP)
• **Oribe, Kazuya**
Minato-ku, Tokyo (JP)
• **Takamido, Hiroshi**
Nagoya-shi, Aichi-ken (JP)

(30) Priority: **08.02.2002 JP 2002032752**

(71) Applicant: **Showa IKA Kohgyo Co., Ltd.**
Aichi-ken (JP)


(74) Representative: **Grünecker, Kinkeldey,**
Stockmair & Schwanhäusser Anwaltssozietät
Maximilianstrasse 58
80538 München (DE)

(54) **Vertebral body distance retainer**

(57) A vertebral body distance retainer comprises a retainer member including engaging portions to be engaged with a pair of rods provided on a plurality of adjacent vertebral bodies and abutting portions capable of freely abutting on spinous processes of the adjacent

vertebral bodies, and fixing screws which fix the rods being engaged with the engaging portions. The vertebral body distance retainer is disposed between the spinous processes each existing on the adjacent vertebral bodies, so that the distance between the spinous processes can be retained constant.

FIG. 2



Description**BACKGROUND OF THE INVENTION****1. Field of the Invention**

[0001] The present invention relates to a vertebral body distance retainer for constantly retaining a distance between spinous processes by disposing the retainer between spinous processes each existing on adjacent vertebral bodies. More specifically, the present invention relates to a vertebral body distance retainer capable of effectively controlling displacement of the vertebral bodies.

2. Description of the Related Art

[0002] A device shown in FIG. 1A and FIG. 1B is known as a proposed vertebral body distance retainer for retaining a distance between spinous processes, which is disposed between the spinous processes each existing on adjacent vertebral bodies. This vertebral body distance retainer 101 has the constitution in which control plates 105 each protruding outward are provided on both end portions of a U-shaped retainer member 103.

[0003] As shown in FIG. 1B, the vertebral body distance retainer 101 has the constitution in which the retainer member 103 is disposed between spinous processes 109 each existing on adjacent vertebral bodies 107 and the control plates 105 provided on the retainer member 103 are engaged with side surfaces of the spinous processes 109.

SUMMARY OF THE INVENTION

[0004] However, since the proposed distance retainer 101 is designed to be simply placed between the spinous processes 109, the distance retainer 101 has a problem in terms of stability upon fixing a position between the vertebral bodies.

[0005] The present invention has been made in consideration of the above problems. It is an object of the present invention to provide a vertebral body distance retainer capable of tightly fixing adjacent vertebral bodies to achieve high stability.

[0006] To achieve the object described above, the present invention provides a vertebral body distance retainer, comprising: a retainer member including engaging portions to be engaged with a pair of rods provided on a plurality of adjacent vertebral bodies, and abutting portions capable of freely abutting on spinous processes of the adjacent vertebral bodies; and fixing screws which fix the rods, the rods being engaged with the engaging portions, wherein the vertebral body distance retainer is disposed between the spinous processes each existing on the adjacent vertebral bodies, so that the distance between the spinous processes can be retained

constant.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The invention will now be described with reference to the accompany drawings wherein;

FIG. 1A and FIG. 1B are schematic views showing a structure of a proposed vertebral body distance retainer;

FIG. 2 is a schematic view showing a structure of a vertebral body distance retainer according to an embodiment of the present invention;

FIG. 3A is a top plan view showing a structure of a vertebral body distance retainer according to an embodiment of the present invention; and

FIG. 3B is a cross-sectional view showing a structure of a vertebral body distance retainer according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0008] Hereinafter, description will be made of embodiments of the present invention with reference to the drawings.

[0009] As shown in FIG. 2, a vertebral body distance retainer 1 according to an embodiment of the present invention is disposed and used between spinous processes 5 each existing on adjacent vertebral bodies 3. Upon fixation thereof, the vertebral body distance retainer 1 is fixed to a pair of rods 7A and 7B, which are disposed so as to sandwich the spinous processes 5.

[0010] FIG. 2 shows a constitution example in which the vertebral body distance retainers 1 are each fitted to both ends of the pair of rods 7A and 7B so that the rods 7A and 7B are fixed by allowing the vertebral body distance retainers 1 to abut respectively on the spaced spinous processes 5. However, as the constitution for fixing the pair of rods 7A and 7B, it is also possible to apply a constitution in which a plurality of implants such as screws are each screwed and fixed to the spaced vertebral bodies 3 so that the both end portions of the rods 7A and 7B are fixed to the plurality of implants. Otherwise, it is also possible to apply a constitution in which a hook is provided on one end of each of the rods 7A and 7B so that each of the hooks is hanged and fixed on a pedicle of vertebral arch existing on the vertebral body. It is possible to apply various types of constitutions for fixing the pair of rods 7A and 7B as appropriate.

[0011] As shown in FIG. 3A and FIG. 3B, the vertebral body distance retainer 1 includes a plate type retainer member 9. On both ends in the width direction of the retainer member 9, abutting portions 11 that can freely abut on the spinous processes 5 are formed. Moreover, outer edges 13 of the abutting portions 11 are each formed into sharp blades so that the outer edges 13 can bite into the spinous processes 5.

[0012] Engaging portions 15 and 17 for engaging with the pair of rods 7A and 7B are provided on a lower side of the retainer member 9 along the longitudinal direction of the retainer member 9 with a space provided therebetween. The engaging portions 15 and 17 are formed so as to have apertures in the same direction. Accordingly, the engaging portions 15 and 17 are each formed into semicircular shapes corresponding to diameters of the pair of rods 7A and 7B. Moreover, fixing screws 19 are screwed in the vicinity of the apertures of the engaging portions 15 and 17, and tip portions (lower end portions) of the fixing screws 19 are formed into tapers which provide taper faces 21 so that the tip portions can freely abut on outer peripheries of the rods 7A and 7B engaged with the engaging portions 15 and 17.

[0013] In the above-described constitution, the retainer member 9 of the vertebral body retainer 1 is disposed between the spinous processes 5 each existing on the adjacent vertebral bodies 3, and the spinous processes 5 are abutted on the abutting portions 11 provided on the both sides of the retainer member 9. Moreover, the engaging portions 15 and 17 provided on the retainer member 9 are engaged with the pair of rods 7A and 7B disposed on the both sides of the spinous processes 5, and then the fixing screws 19 are tightened. In this way, the rods 7A and 7B, and the retainer member 9 are integrated.

[0014] When the pair of rods 7A and 7B is integrated with the retainer member 9 as described above, the distance between the rods 7A and 7B are retained constantly by the retainer member 9, and movements of the rods 7A and 7B are thereby controlled. In other words, in the state where the both end portions of the rods 7A and 7B are fixed to the spaced vertebral bodies 3 with the implants such as a plurality of screws provided therebetween, the retainer member 9 is fixed to the rods 7A and 7B.

[0015] Therefore, the vertebral bodies 3 in the spaced positions are retained in the constant distance with the rods 7A and 7B fixed thereto, and the distance between the spinous processes 5 located on the both sides of the retainer member 9 are controlled by the retainer member 9. Accordingly, movements of the vertebral bodies 3 toward a mutually approaching direction are controlled. Moreover, in the state where the blades provided on the both side portions of the retainer member 9 bite slightly into the spinous processes 5, relative movements of the adjacent spinous processes 5 are restricted, whereby displacement of the vertebral bodies 3 is effectively controlled.

[0016] Moreover, when the rods 7A and 7B are fixed to the engaging portions 15 and 17 by tightening the fixing screws 19, the rods 7A and 7B are tightly pressed into the engaging portions 15 and 17 by wedge effects of the taper faces 21 provided on the fixing screws 19. Furthermore, the fixing screws 19 are located in the positions which are shifted inward from the central axes of the rods 7A and 7B, i.e. toward the aperture sides.

Hence, the taper faces 21 provided on the tip portions of the fixing screws 35 abut on the outer peripheries of the rods 7A and 7B when the fixing screws 35 are tightened and act to press the rods 7A and 7B obliquely downward. Accordingly, the rods 7A and 7B can be surely fixed by pressure into inner peripheries of the engaging portions 15 and 17. In addition, the tip portions of the fixing screws 19 narrow the apertures of the engaging portions 15 and 17, whereby the rods 7A and 7B can be surely fixed to the engaging portions 15 and 17.

[0017] Furthermore, in the above-described constitution, the engaging portions 15 and 17 provided on the retainer member 9 have the apertures in the same direction. Therefore, it is possible to engage and detach the engaging portions 15 and 17 to and from the pair of rods 7A and 7B simultaneously. In this way, engagement and detachment can be facilitated.

[0018] As will be understood from the foregoing description, according to the present invention, the retainer member disposed between the spinous processes can be fixed integrally to the pair of rods disposed on the both sides of the spinous processes. Moreover, it is possible to allow the blades provided on the both sides in the width direction of the retainer member to bite into the spinous processes. Therefore, the distance between the spinous processes can be stably retained while controlling movements of the spinous processes, whereby the problem of the proposed art as described above will be satisfactorily resolved.

[0019] The entire content of a Japanese Patent Application No. P2002-32752 with a filing date of February 8, 2002 is herein incorporated by reference.

[0020] Although the invention has been described above by reference to certain embodiments of the invention, the invention is not limited to the embodiments described above will occur to those skilled in the art, in light of the teachings. The scope of the invention is defined with reference to the following claims.

Claims

1. A vertebral body distance retainer, comprising:

a retainer member including engaging portions to be engaged with a pair of rods provided on a plurality of adjacent vertebral bodies, and abutting portions capable of freely abutting on spinous processes of the adjacent vertebral bodies; and
fixing screws which fix the rods, the rods being engaged with the engaging portions,

wherein the vertebral body distance retainer is disposed between the spinous processes each existing on the adjacent vertebral bodies, so that the distance between the spinous processes can be retained constant.

2. The vertebral body distance retainer of claim 1,
wherein the abutting portion is provided with
a blade capable of biting into the spinous process.
3. The vertebral body distance retainer of claim 1, 5
wherein the fixing screw is provided with a ta-
per face at a tip portion thereof, the taper face being
configured to abut on an outer peripheral face of the
rod located in the engaging portion. 10
4. The vertebral body distance retainer of claim 1,
wherein the fixing screw is located in a posi-
tion being shifted from a central axis of the rod en-
gaged with the engaging portion toward an aperture
of the engaging portion. 15

20

25

30

35

40

45

50

55

FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A





FIG. 3B





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 334 703 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
31.03.2004 Bulletin 2004/14

(51) Int Cl.7: **A61F 2/44, A61B 17/70**

(43) Date of publication A2:
13.08.2003 Bulletin 2003/33

(21) Application number: **03002588.6**

(22) Date of filing: **07.02.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT SE SI SK TR**
Designated Extension States:
AL LT LV MK RO

(72) Inventors:
• **Nekozuka, Yoshio**
Sapporo-shi, Hokkaido (JP)
• **Oribe, Kazuya**
Minato-ku, Tokyo (JP)
• **Takamido, Hiroshi**
Nagoya-shi, Aichi-ken (JP)

(30) Priority: **08.02.2002 JP 2002032752**

(71) Applicant: **Showa IKA Kohgyo Co., Ltd.**
Aichi-ken (JP)


(74) Representative: **Grünecker, Kinkeldey,
Stockmair & Schwanhäusser Anwaltssozietät
Maximilianstrasse 58
80538 München (DE)**

(54) **Vertebral body distance retainer**

(57) A vertebral body distance retainer comprises a retainer member including engaging portions to be engaged with a pair of rods provided on a plurality of adjacent vertebral bodies and abutting portions capable of freely abutting on spinous processes of the adjacent

vertebral bodies, and fixing screws which fix the rods being engaged with the engaging portions. The vertebral body distance retainer is disposed between the spinous processes each existing on the adjacent vertebral bodies, so that the distance between the spinous processes can be retained constant.

FIG. 2





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 00 2588

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 947 966 A (BRUMFIELD DAVID L ET AL) 7 September 1999 (1999-09-07) * column 4, line 25 - line 58 * * column 5, line 64 - column 6, line 19 * * figures 1,2,10 * ---	1-4	A61F2/44 A61B17/70
X	WO 01 91657 A (ST FRANCIS MEDICAL TECHNOLOGIE) 6 December 2001 (2001-12-06) * page 67, line 16 - page 83, line 27 * * figures 130-151 * ---	1	
X	US 5 725 582 A (BEVAN DAVID ROBIN ET AL) 10 March 1998 (1998-03-10) ---	1	
A	* the whole document * ---	2-4	
A	FR 2 738 143 A (CAHLIK MARC ANDRE) 7 March 1997 (1997-03-07) * column 7, line 4 - line 9 * * figures 16A,16C * ---	1,2	
A	FR 2 704 420 A (INNOVATIONS TECHNOLOGIQUES STE) 4 November 1994 (1994-11-04) * the whole document * ---	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7) A61B A61F
A	US 4 289 123 A (DUNN HAROLD K) 15 September 1981 (1981-09-15) * column 3, line 17 - column 4, line 5 * * figures * -----	1	
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 5 February 2004	Examiner Nistor, L
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

EPO FORM 1503 03/82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 00 2588

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-02-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5947966	A	07-09-1999	US 6136003 A	24-10-2000
			AU 2064697 A	16-09-1997
			WO 9731580 A1	04-09-1997
			AT 251423 T	15-10-2003
			AU 5935196 A	24-12-1996
			DE 69630317 D1	13-11-2003
			EP 0874594 A1	04-11-1998
			JP 2000501624 T	15-02-2000
			WO 9639090 A1	12-12-1996
			US 6402751 B1	11-06-2002
			US 6113600 A	05-09-2000
WO 0191657	A	06-12-2001	US 6451019 B1	17-09-2002
			US 6235030 B1	22-05-2001
			US 6048342 A	11-04-2000
			US 6190387 B1	20-02-2001
			US 6068630 A	30-05-2000
			AU 6348001 A	11-12-2001
			AU 6508001 A	11-12-2001
			WO 0191657 A1	06-12-2001
			WO 0191658 A1	06-12-2001
			US 2002029039 A1	07-03-2002
			US 2002116000 A1	22-08-2002
			WO 0207623 A1	31-01-2002
			US 2002091446 A1	11-07-2002
			US 2002143331 A1	03-10-2002
			US 6332883 B1	25-12-2001
			US 2001012938 A1	09-08-2001
			US 2001020170 A1	06-09-2001
			US 2001021850 A1	13-09-2001
			US 2002111679 A1	15-08-2002
			US 2002099377 A1	25-07-2002
			US 2002072752 A1	13-06-2002
			AU 737486 B2	23-08-2001
			AU 1365999 A	17-05-1999
			CA 2307888 A1	06-05-1999
			EP 1027004 A1	16-08-2000
			JP 2003523214 T	05-08-2003
			WO 9921501 A1	06-05-1999
			US 2003065330 A1	03-04-2003
			US 2002183746 A1	05-12-2002
			AU 750662 B2	25-07-2002
			AU 1362499 A	17-05-1999
			CA 2307878 A1	06-05-1999
			CN 1280473 T	17-01-2001
			EP 1030615 A1	30-08-2000

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 00 2588

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-02-2004

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0191657 A		JP 2001520912 T	06-11-2001
		WO 9921500 A1	06-05-1999
		US 6332882 B1	25-12-2001

US 5725582 A	10-03-1998	CA 2142836 A1	03-03-1994
		DE 69323636 D1	01-04-1999
		DE 69323636 T2	01-07-1999
		EP 0768843 A1	23-04-1997
		ES 2129522 T3	16-06-1999
		WO 9404088 A1	03-03-1994
		GB 2269753 A ,B	23-02-1994
		JP 8502668 T	26-03-1996
		KR 275162 B1	15-12-2000

FR 2738143 A	07-03-1997	FR 2738143 A1	07-03-1997

FR 2704420 A	04-11-1994	FR 2704420 A1	04-11-1994

US 4289123 A	15-09-1981	AU 6883281 A	08-10-1981

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82